

Panasonic

Premium LED HDTVs for Guest Room Entertainment

LED



Hospitality LED HDTV Line-Up



TH-32LRU7 **NEW**



TH-39LRU6



TH-42LRU7 **NEW**

Integrated LED HDTVs

The LRU7/6 Series with built-in Pro:Idiom features an elegant, slim-bezel design. Our lineup of hospitality displays enhances any guest room or suite.

New Energy-Saving Design

Designed with the latest Energy Star® specifications, each LED backlight display features innovative energy-saving functions (e.g. C.A.T.S.) that greatly reduce power consumption while ensuring optimal performance.

Simple, Easy Installation

Installation and management are simplified with a built-in terminal adaptor and centralized FTG channel management. The narrow bezel and space-saving design gives you more screen size without taking up more space when replacing older models.

Specifications

	TH-42LRU7	TH-39LRU6	TH-32LRU7
DISPLAY			
Screen Size	41.9 -inch	38.5 -inch	31.5 -inch
Panel	LCD Panel / D-LED	1080p (WSXGA) LED	LCD Panel / D-LED
Effective Display Area	36.5" x 20.5" (928 x 522 mm)	32.6" x 18.9" (854 x 480 mm)	27.4" x 15.4" (698 x 392 mm)
Number of Pixels (H x V)	1,920 x 1,080 pixel	1,920 x 1,080 pixel	1,366 x 768 pixel
Panel Life	Approx. 60,000 hours	Approx. 60,000 hours	Approx. 60,000 hours
Brightness (Panel)	350 cd/m ²	300 cd/m ²	350 cd/m ²
Intelligent Scene Controller	Yes	Yes	Yes
RECEIVING SYSTEM			
ATSC/NTSC/QAM	VHF/ UHF: 2 - 69, CATV: 1 - 135	VHF/ UHF: 2 - 69, CATV: 1 - 135	VHF/ UHF: 2 - 69, CATV: 1 - 135
FTG Pro: Idiomi HD Support	Local Authentication by USB Memory	Local Authentication by USB Memory	Local Authentication by USB Memory
CONNECTION TERMINAL			
RF In (Antenna/Cable)	1	1	1
Video In	RCA x 1 (Rear)	RCA x 1 (Rear), RCA x 1 (Side)	RCA x 1 (Rear)
Audio In (L/R)	RCA x 1 set (Rear [Share with Component])	RCA x 1 set (Rear [Share with Component]), x 1 set (Side)	RCA x 1 set (Rear [Share with Component])
Component Video In	RCA x 1 set (Y Pb Pr) (Rear)	RCA x 1 set (Y Pb Pr) (Rear)	RCA x 1 set (Y Pb Pr) (Rear [Share with Video])
Audio In (L/R)	RCA x 1 set (Rear)	RCA x 1 set (Rear)	RCA x 1 set (Rear)
HDMI In	HDMI Type A Connector x 2 (Rear), x 1 (side)	HDMI Type A Connector x 2 (Rear), x 1 (side)	HDMI Type A Connector x 2 (Rear), x 1 (side)
PC In	Mini D-Sub 15-pin x 1 (Female, Rear)	Mini D-Sub 15-pin x 1 (Female, Rear)	Mini D-Sub 15-pin x 1 (Female, Rear)
Audio In (L/R)	M3 jack x 1 (Rear)	M3 jack x 1 (Rear)	M3 jack x 1 (Rear)
Audio Out (Digital / SPDIF)	Optical x 1 (Rear)	—	Optical x 1 (Rear)
Audio Out (Analog L/R)	M3 jack x 1 (Rear)	M3 jack x 1 (Rear)	M3 jack x 1 (Rear)
USB Memory Slot	USB2.0 Type A Connector x 1 (Side)	1	USB2.0 Type A Connector x 1 (Side)
CONTROL TERMINAL			
DATA / MTI	RJ-11(6-pin) x 1 (Rear)	RJ-11(6-pin) x 1 (Rear)	RJ-11(6-pin) x 1 (Rear)
Serial Port	M3 jack x 1 (Rear), RS232C	M3 jack x 1 (Rear), RS232C	M3 jack x 1 (Rear), RS232C
Ethernet	RJ45 x 1 (Rear)	—	RJ45 x 1 (Rear)
ELECTRICAL			
Power Requirements	110-127 V AC, 60 Hz	110-127 V AC, 60 Hz	110-127 V AC, 60 Hz
Power Consumption	105 W	80 W	70 W
On Mode Average Power Consumption*	37.1 W (Energy star 6.1, CEC)	34.3 W (Energy star 6.0, CEC)	24.1 W (Energy star 6.1, CEC)
Stand-by Power	Under 1.0 W	Under 1.0 W	Under 1.0 W
AUDIO			
Audio Output Power	10 W + 10 W (10 % THD)	10 W + 10 W (10 % THD)	10 W + 10 W (10 % THD)
Invisible Speaker System Details	1 Way 2 Bottom Speakers	1 Way 2 Bottom Speakers	1 Way 2 Bottom Speakers
DIMENSIONS & WEIGHT			
TV with Stand (W x H x D)	38.0" x 24.8" x 9.9"	35.3" x 24.4" x 9.0"	28.9" x 19.7" x 9.9"
TV without Stand (W x H x D)	38.0" x 22.3" x 3.0"	35.3" x 21.2" x 3.3"	28.9" x 17.2" x 2.8"
TV with Stand Weight	24.5 lbs.	23.4 lbs.	15.3 lbs.
TV without Stand Weight	18.8 lbs.	19.9 lbs.	11.5 lbs.
STANDARD (CERTIFICATIONS)			
Safety Regulations	UL6500 Ver.2, cUL, BETS-7	UL6500 Ver.2, cUL, BETS-7	UL6500 Ver.2, cUL, BETS-7
Radiation Regulations	FCC Part 15 Class-B, ICES-003	FCC Part 15 Class-B, ICES-003	FCC Part 15 Class-B, ICES-003

*Based on IEC 62087Ed.2 section 11.6.1 measurement method.

Features

- VIERA Link™, HDAVI Control™
- Integrated Pro: Idiomi
- USB Slot (Image Viewer (JPEG, Playback), Cloning)
- Hotel Mode
- Welcome Image
- Local Authentication
- Remote Stand (30/ 60/ 90 degree)

Ambient Light Sensor | Automatically adjusts the image quality for each room based on room lighting, while saving energy.

The LRU7/6 Series' built-in ambient light sensor (C.A.T.S.) automatically adjusts the television's screen brightness, color and contrast to suit the lighting of the room. This not only optimizes picture performance, but it also helps keep power consumption low — so you can maximize your guests' experience while saving on energy costs.



LRU7/6 C.A.T.S.
C.A.T.S. [Contrast Automatic Tracking System] maintains brightness levels and optimizes image quality while reducing power consumption.

Panasonic®



For more information about Panasonic Professional Displays, please visit:
Professional Display Global Website – panasonic.net/prodisplays
YouTube – www.youtube.com/PanasonicProDisplay

Weights and dimensions shown are approximate. Specifications and appearance are subject to change without notice. Product availability differs depending on region and country. This product may be subject to export control regulations. All other trademarks are the property of their respective trademark owners. Images on screen are simulated. © 2014 Panasonic Corporation. All rights reserved.

All information included here is valid as of May 2014.

CT14-U02PF-LRU Printed in Japan.